

BLCOM Nanobubble Generator



TYPICAL APPLICATIONS

- Deep Water Culture
- Shallow Water Culture
- NFT
- Drip Irrigation
- Inline Aeration
- Water Tank Aeration
- Reservoir Aeration
- Algae Control
- Biofilm Control

The patent-pending Moleaer Bloom is a highly efficient gas-injection technology that converts bulk oxygen into nanobubbles and supersaturates irrigation water with high levels of dissolved oxygen (DO). Negatively charged, neutrally buoyant nanobubbles can remain suspended in water for long periods of time, acting like an oxygen battery that delivers oxygen to the entire body of water. As oxygen is consumed, the nanobubbles continue to diffuse more oxygen into solution, sustaining supersaturated levels of DO, even in warm water. Moleaer's Bloom is an economical and highly effective tool to improve water quality, increase plant growth, and suppress root disease and environmental stress.

The Bloom comes with a self-priming, enclosed impeller pump for maximum flow and energy efficiency. The system is whisper-quiet and corrosion-resistant. The Bloom can be upgraded with a smart controller and integrated DO sensor to allow real time monitoring and system control. Available in 25, 50 and 150 gpm flow rates, the Bloom was designed for durable operation, easy installation, and simple control.

FEATURES & BENEFITS

- 90% standard oxygen transfer efficiency
- Supersaturated irrigation water
- Improved water quality
- 100 nm-sized bubbles produced in excess of 1 billion nanobubbles / ml
- Oxygenation of any tank and any depth of water
- Increased nutrient adsorption
- Promotion of beneficial bacteria, suppression of pathogens
- Easy integration with fertigation and climate control systems.
- Optional: DO monitoring, system controller, and low-gas pressure warning

www.moleaer.com

The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. Moleaer assumes no liability for results obtained or damages incurred through the application of the information contained herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. Copyright © 2017 Moleaer. All trademarks stated herein are the property of their respective company. All rights reserved.



MODELS	Bloom 25	Bloom 50	Bloom 150
LIQUID FLOW CAPACITY		// //	
Flow Rate, GPM (m ³ /hr)	25 (6)	50 (11)	150 (134)
Indicated Gas Flow Range Maximum, CFH (m ³ /hr)	2.5 (0.07)	5 (0.14)	15 (0.424)
Indicated Gas Flow Range Recommended, CFH (m ³ /hr)	0.25 (0.011)	0.5 (0.01)	1.5 (0.042)
OPERATING PARAMETERS			
Temperature Tolerance, PVC, °F (°C)		41 - 140 (5 - 60)	
Standard Oxygen Transfer Efficiency		> 90%	
Solids, inches (mm)		Up to 3/8 (10)	
GAS FEED ¹			
Feed Gas Pressure Range Minimum, PSIG (bar)	100 (6.89)		
Feed Gas Pressure Range Maximum, PSIG (bar)	140 (9.65)		
PUMP			
Pump Model	Pentair Sparus 160		
Wetted Parts Materials	Polypropylene/316 SS/Buna		
Pump Motor, hp (kW)	0.5 (0.37)		3 (2.2)
Voltage	115/208-230		115/208-230
FL Amp	8.8	8 / 4.5-4.4	15 - 13.6
Phase		1	
Frequency, Hz		60	
CONTROLS			
NEMA 12R Pro Controller		Timed Start / Stop	
	20 Times / Day		
Voltage	12V AC		
Communications	MODBUS Remote Connection		
Power (Light)	On/Off DP		
Motor Starter	20 Amp W OL (120V)		
Start Switch	Latching (12V DC)		
Gas Pressure Alarm with Light	On/Off (12V DC)		
Pressure Gauges		Wika 2.5" (60/160)	
Rotameter, CFH	0 - 2.5	0 - 5	0 - 10
Dissolved Oxygen (DO) Sensor ²	Optical,	0 - 50 ppm (+/- 1.5 ppm), 30 Second Res	ponse Time
CONNECTIONS - FNTP			
Inlet, inches	2	2	2
Discharge, inches	1	1.5	2
Air Fitting for External Compressor, inches		1/4 Industrial	
DIMENSIONS & WEIGHT			
Height, inches (cm)		28 (71.12)	
Width, Inches (cm)	14 (35.56)		
Length, inches (cm)	32 (81.28)		
Weight, Ib (kg)	130 (59)		150 (68)

Note 1: When using oxygen, Moleaer recommends CGA inlet 540, outlet 9/16" - 18RH pressure regulator with delivery range of 5-150 PSI (0.34-10.3 bar). Note 2: Bloom IQ Option Integrated Dissolved Oxygen Optical Sensor Probe





www.moleaer.com

The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. Moleaer assumes no liability for results obtained or damages incurred through the application of the information contained herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. Copyright © 2017 Moleaer. All trademarks stated herein are the property of their respective company. All rights reserved.