

BLOOM Nanobubble Generator



TYPICAL APPLICATIONS

- Deep Water Culture
- Shallow Water Culture
- NFT
- Drip Irrigation
- Inline Aeration
- Water Tank Aeration
- Reservoir Aeration
- Algae Control
- Biofilm Control

The patent-pending Moleaer Bloom is a highly efficient gas-injection technology that converts bulk oxygen into nanobubbles and supersaturates irrigation water with high levels of dissolved oxygen (DO). Negatively charged, neutrally buoyant nanobubbles can remain suspended in water for long periods of time, acting like an oxygen battery that delivers oxygen to the entire body of water. As oxygen is consumed, the nanobubbles continue to diffuse more oxygen into solution, sustaining supersaturated levels of DO, even in warm water. Moleaer's Bloom is an economical and highly effective tool to improve water quality, increase plant growth, and suppress root disease and environmental stress.

The Bloom comes with a self-priming, enclosed impeller pump for maximum flow and energy efficiency. The system is whisper-quiet and corrosion-resistant. The Bloom can be upgraded with a smart controller and integrated DO sensor to allow real time monitoring and system control. Available in 25, 50 and 150 gpm flow rates, the Bloom was designed for durable operation, easy installation, and simple control.

FEATURES & BENEFITS

- 90% standard oxygen transfer efficiency
- Supersaturated irrigation water
- Improved water quality
- 100 nm-sized bubbles produced in excess of 1 billion nanobubbles / ml
- Oxygenation of any tank and any depth of water
- Increased nutrient adsorption
- Promotion of beneficial bacteria, suppression of pathogens
- Easy integration with fertigation and climate control systems.
- Optional: DO monitoring, system controller, and low-gas pressure warning

www.moleaer.com

MODELS	Bloom 25	Bloom 50	Bloom 150
LIQUID FLOW CAPACITY			
Flow Rate, GPM (m ³ /hr)	25 (6)	50 (11)	150 (134)
Indicated Gas Flow Range Maximum, CFH (m ³ /hr)	2.5 (0.07)	5 (0.14)	15 (0.424)
Indicated Gas Flow Range Recommended, CFH (m ³ /hr)	0.25 (0.011)	0.5 (0.01)	1.5 (0.042)
OPERATING PARAMETERS			
Temperature Tolerance, PVC, °F (°C)		41 - 140 (5 - 60)	
Standard Oxygen Transfer Efficiency		> 90%	
Solids, inches (mm)		Up to 3/8 (10)	
GAS FEED¹			
Feed Gas Pressure Range Minimum, PSIG (bar)		100 (6.89)	
Feed Gas Pressure Range Maximum, PSIG (bar)		140 (9.65)	
PUMP			
Pump Model		Pentair Sparus 160	
Wetted Parts Materials		Polypropylene/316 SS/Buna	
Pump Motor, hp (kW)	0.5 (0.37)		3 (2.2)
Voltage	115/208-230		115/208-230
FL Amp	8.8 / 4.5-4.4		15 - 13.6
Phase		1	
Frequency, Hz		60	
CONTROLS			
NEMA 12R Pro Controller		Timed Start / Stop 20 Times / Day	
Voltage		12V AC	
Communications		MODBUS Remote Connection	
Power (Light)		On/Off DP	
Motor Starter		20 Amp W OL (120V)	
Start Switch		Latching (12V DC)	
Gas Pressure Alarm with Light		On/Off (12V DC)	
Pressure Gauges		Wika 2.5" (60/160)	
Rotameter, CFH	0 - 2.5	0 - 5	0 - 10
Dissolved Oxygen (DO) Sensor ²		Optical, 0 - 50 ppm (+/- 1.5 ppm), 30 Second Response Time	
CONNECTIONS - FNTF			
Inlet, inches	2	2	2
Discharge, inches	1	1.5	2
Air Fitting for External Compressor, inches		1/4 Industrial	
DIMENSIONS & WEIGHT			
Height, inches (cm)		28 (71.12)	
Width, inches (cm)		14 (35.56)	
Length, inches (cm)		32 (81.28)	
Weight, lb (kg)	130 (59)		150 (68)

Note 1: When using oxygen, Moleaer recommends CGA inlet 540, outlet 9/16" - 18RH pressure regulator with delivery range of 5-150 PSI (0.34-10.3 bar).

Note 2: **Bloom IQ Option** Integrated Dissolved Oxygen Optical Sensor Probe

